



ACCEPTED PRODUCTS

TA 50 manufacturer shall be specialist in this type of work, having been in operation as a company for a minimum of 3 years.

TA 50 shall be steel (kd or all welded) as produced by Major Partitions.

Quantities, and sizes and arrangements shall be show on drawings.

SUBMITTALS

Submit shop drawings of wire mesh partitions prior to fabrication. Shop drawings shall clearly show and describe in detail, materials, connections, attachments, anchorage, elevations, dimensions and thicknesses of materials.

MATERIALS

PANELS

Panels shall be 10g wire 1"x2" welded mesh welded into an angle frame of 1 ¼ x 1 ¼ x 10g angle welded at every 8 inches.

DOUBLE SWING DOORS

Frames shall be 1 ¼" x 1 ¼" x 10g angle with 2" x 1" x 10 gauge rectangular steel mesh welded to frame equipped with a 3 point turn handle for padlock.

BACKS

16 gauges painted steel.

SHELVES/BOTTOMS

Formed 16g sheet metal.

COAT ROD

1" zinc plated pipe with mounting brackets.

COAT HOOKS

2 hooks per unit attached to shelf.

FINISH

Baked grey powder over a phosphate treated steel.

EXECUTION

Erect TA 50 in accordance to reviewed shop drawings and manufacturer's recommendations.

Clean damaged or scratched surfaces with touch up paint as recommended by manufacturer.